



SD17.2



SD13.2



SD6CX



SD6S.2

Model	SD10.2	SD13.2	SD17.2	SD6S.2	SD6CX	SD6CX
Peak	150W	175W	225W	400W	250W	250W
Continuous Input Power	45W	52W	67W	125W	80W	80W
Sensitivity (1W/1m)	86dB	86dB	87dB	91dB	85dB	85dB
Frequency Response	65Hz-20KHz	75Hz-20KHz	65Hz-20KHz	25Hz-20KHz	65Hz-20KHz	65Hz-20KHz
Impedance	4Ω x 1	4Ω x 1	4Ω x 1	4Ω x 1	4Ω x 1	4Ω x 1
Warranty	3Yrs	3Yrs	3Yrs	3Yrs	3Yrs	3Yrs
Speaker Size	6 1/2" Dia	6 1/2" Dia	6 7/8" Dia	6 1/2" Dia	6 1/2" Dia	6 1/2" Dia



EDE602



EDE603



EDE6903



EDE402

Model	EDE402	EDE602	EDE602	EDE6903	EDE185K	EDE120K
Peak	80W	100W	100W	100W	100W	100W
Continuous Input Power	30W	40W	40W	40W	40W	40W
Sensitivity (1W/1m)	87dB	86dB	86dB	86dB	86dB	86dB
Frequency Response	65Hz-20KHz	65Hz-20KHz	65Hz-20KHz	65Hz-20KHz	65Hz-20KHz	65Hz-20KHz
Impedance	4Ω x 1	4Ω x 1	4Ω x 1	4Ω x 1	4Ω x 1	4Ω x 1
Warranty	3Yrs	3Yrs	3Yrs	3Yrs	3Yrs	3Yrs



### HM165K

- Stronger power 3-way components
- woofer 6.5"/165mm with aluminum basket and carbon fiber cone
- Full-range driver 3"(80mm) with paper cone
- 28mm voice coil silk dome tweeter
- Max power 250W/RMS power 100W
- Frequency response 45Hz-25KHz
- Sensibility 92dB
- Impedance 4 Ohms

[dolen@dgauthentic.com](mailto:dolen@dgauthentic.com)